

BEST-SPINDLE

产品目录 (Product catalogue)

1.ZD3000 系列 (ZD3000 series)

传统一体式内胆结构,稳定可靠,被大规模应用于纺纱。

适纺速度:8000~16500RPM使用寿命:6~8年

Description:

standard traditional design with one piece insert.Stable and reliable.

Being applied to spinning on a large scale. Recommended for speeds :8000~16500 RPM Recommended for spindle lift :6~8 years

Can be supplied for traditional ring spinning machine Weave diameter: 20.2 20.5 22 24(mm)



2.ZD4000 系列 (ZD4000 series)

在传统ZD3000 系列锭子基础上加入纵向吸振弹簧,可用于集体落纱细纱机.

适纺速度:8000~18000RPM(光杆) 6000~19000 (铝杆) 使用寿命:6~8年

Description:

Standard SKF design with one piece insert with spring. Suit for Auto doffer ring spinning machine Recommended for speeds:8000~18000 RPM (Bare blade type) 6000~19000 RPM (ALU type) Recommended for spindle lift: 6~8 years

Can be supplied for can be supplied for each type of ring spinning machine Weave diameter: 18.5 19 20.2 20.5 22(mm)



3.ZD7000 系列锭子 (ZD7000 series)

使用HPS68 一体式双轴承结构, 适合高速。

适纺速度:8000~19000RPM(光杆) 8000~22000 (铝杆) 使用寿命:10年

DESCRIPTION:

Standard HPS 68 design with one piece insert and two bearing levels. Suit for high speed Recommended for speeds:8000~19000 RPM (Bare blade type) 8000~22000 RPM (ALU type)

Recommended for spindle lift: 10 years

Can be supplied for can be supplied for high speed ring spinning machine Weave diameter: 18.5 19 20.2 20.5



4. ZD8000 系列内锭钩锭子 (ZD8000 Series Internal lock)

配用于意大利马佐里细纱机. 使用内锭钩结构. 延长补油换油周期, 防止灰尘进入, 延长锭子使用寿命。

Suit for Italy Marzouli ring spinning Machine.



5. ZD4000G 系列锭子 (ZD4000G series)

光杆集落纱锭子，在传统ZD4000系列锭子上加上弹簧猫眼或离心猫眼，适用于传统细纱机的集体落纱改造，改造中不需要更换纱管和纲领，降低纺纱厂改造成本
配用优质割纱器适当工艺可以适用于5支纱线。

适纺速度: 8000~18000RPM 使用寿命: 8年

DESCRIPTION:

Bare blade type spindle Standard SKF design with one piece insert with spring clutches. Or centrifugal clutches. Suit for ring spinning machine Auto Doffer improvement. No need to change the bobbin and ring. Save modification cost.

Recommended for speeds: 8000~18000 RPM

Recommended for spindle lift: 8 years

6.ZD7000Y 系列龙牙夹纱器锭子 (ZD7000Y CROCO Doff Series Spindle)

新型结构一体化内胆，双轴承，适合高速，配用NOVIBRA龙牙夹纱器，无尾纱，提高留头率，节能降耗。

适纺速度:8000~19000RPM(光杆) 8000~22000 (铝杆) 使用寿命: 10年

DESCRIPTION:

Standard HPS 68 design with one piece insert and two bearing levels. Use Novibra crocodoff Suit for high speed. Opening and closing of cutting crown by centrifugal force No Uncontrolled yarn-end flying、reduction of yarn breakage、reduction of energy consumption、less cleaning

Recommended for speeds: 8000~22000 RPM (ALU type)

Recommended for spindle lift: 10 year



7. ZD9000 系列龙带锭子 (ZD8000 Series Apron Belt Spindle)

配套适用青泽系列细纱机，
Suit for Zinser Ring Spinning Machine.



Different yarn break

